

Guillotines Comparisons Chart

Model	EBA 4815	EBA 4850	EBA 4855	EBA 5255	EBA 6655
Cutting length, mm	475	475	475	520	650
Cutting height, mm	80	80	80	80	80
Narrow cut, mm	30	30	35	35	25
Table depth, mm	458	458	450	520	610
Blade drive	electromechanical	electromechanical	electromechanical	electromechanical	electromechanical
Clamping system	manual spindle clamp	automatic clamp	automatic clamp	automatic clamp	automatic clamp
Backgauge	manual	manual	electric	electric	electric
Manual backgauge setting	hand crank	hand crank	electronic hand wheel	electronic hand wheel	electronic hand wheel
Measurement indication (mm/inches)	digital display	digital display	digital display	digital display	digital display
Electronic control for backgauge	-	-	touch pad	touch pad	touch pad
Program mode	-	-	99 programs, 99 steps	99 programs, 99 steps	99 programs, 99 steps
Blade made of German high quality steel	•	•	•	•	•
Optical cutting line indicator (LEDs)	•	•	•	•	•
Electronically controlled front safety cover	•	•	•	•	•
Practical stand and storage shelf	•	•	•	•	•
EASY-CUT (patented blade activating bars)	•	•	•	•	•
Practical hook-in tool holder on back table	•	•	•	•	•
Optional accessories (at an extra cost)	set of side tables	set of side tables	set of side tables	set of side tables	set of side tables
Dimensions, mm (H x W x D)	1410 x 762/1349 ¹ x 1053	1296 x 762/1349 ¹ x 1053	1296 x 762/1349 ¹ x 1053	1293 x 860/1436 ¹ x 1120	1293 x 992/1565 ¹ x 1220
Power supply ²	230 V / 50 Hz / 1.1 kW	230 V / 50 Hz / 1.42 kW	230 V / 50 Hz / 1.42 kW	230 V / 50 Hz / 1.42 kW	230 V / 50 Hz / 1.42 kW
Weight, kg	212 / 221 ¹	225 / 234 ¹	228 / 237 ¹	252 / 261 ¹	302 / 311 ¹



JB Binding Ltd, Caherconreefy, Pallasgreen, Co Limerick

Contact: John Byrnes 087 6888600: Office 061 513500: Email john@jbbinding.ie : Web www.jbbinding.ie